



Gradiminiparete led retinato



22 cm
8^{5/8}"




25,5 cm
6"

26 cm
6^{2/4}"



luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025


light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	




versions



Gradiminiparete led retinato
chrome
cod 516L




Gradiminiparete led retinato
satin nickel-plated
cod 586L



Gradiminiparete led opalescente
chrome
cod 527L



Gradiminiparete led opalescente
satin nickel-plated
cod 587L




Gradiminiparete led tuttopallescente
chrome
cod 581L




Gradiminiparete led tuttopallescente
satin nickel-plated
cod 588L

Gradiminiparete led opalescente




22 cm
8^{5/8}"





25,5 cm
6"

26 cm
6^{2/4}"




luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE  (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025


light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	



versions



Gradiminiparete led retinato chrome
cod 516L



Gradiminiparete led retinato satin nickel-plated
cod 586L



Gradiminiparete led opalescente chrome
cod 527L



Gradiminiparete led opalescente satin nickel-plated
cod 587L




Gradiminiparete led tuttopallescente chrome
cod 581L




Gradiminiparete led tuttopallescente satin nickel-plated
cod 588L

Gradiminiparete led

tuttopalescente




22 cm
8^{5/8}"





25,5 cm
6"

26 cm
6^{3/4}"




	luminaire
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	wall
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE  (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025


	light source
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	




versions




Gradiminiparete led retinato
chrome
cod 516L




Gradiminiparete led retinato
satin nickel-plated
cod 586L



Gradiminiparete led opalescente
chrome
cod 527L



Gradiminiparete led opalescente
satin nickel-plated
cod 587L





Gradiminiparete led tuttopalescente
chrome
cod 581L



Gradiminiparete led tuttopalescente
satin nickel-plated
cod 588L

Gradiminisoffitto led retinato



28,5 cm
7^{2/4}"


22 cm
8^{5/8}"

Ø 22 cm
Ø 4^{3/4}"



luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	ceiling
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025

light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	



versions



Gradiminisoffitto led retinato
chrome
cod 518L



Gradiminisoffitto led retinato
satin nickel-plated
cod 520L



Gradiminisoffitto led opalescente
chrome
cod 529L



Gradiminisoffitto led opalescente
satin nickel-plated
cod 589L





Gradiminisoffitto led tuttopallescente
chrome
cod 583L



Gradiminisoffitto led tuttopallescente
satin nickel-plated
cod 585L

Gradiminisoffitto led

opalescente



28,5 cm
7^{2/4}"


22 cm
8^{5/8}"

Ø 22 cm
Ø 4^{3/4}"



luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	ceiling
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025

light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	



versions



Gradiminisoffitto led retinato
chrome
cod 518L



Gradiminisoffitto led retinato
satin nickel-plated
cod 520L



Gradiminisoffitto led opalescente
chrome
cod 529L



Gradiminisoffitto led opalescente
satin nickel-plated
cod 589L





Gradiminisoffitto led tuttopallescete
chrome
cod 583L



Gradiminisoffitto led tuttopallescete
satin nickel-plated
cod 585L

Gradiminisoffitto led

tuttopalescente





28,5 cm
7^{2/4}"

22 cm
8^{5/8}"

Ø 22 cm
Ø 4^{3/4}"



luminaire	
materials	steel, zama, borosilicate glass
environment	interiors
mounting location	ceiling
emission	indirect light
weight	0,6 kg
voltage	230V
ballast	dimmable electronic integrated
dimmer	phase-cut
insulation class	2
IP classification	IP20
certifications	CE  (pending)
design	Franco Bettonica, Mario Melocchi, 2990/2025

light source	
source	LED
number of led	2
power	2x6W
luminous flux	2x750 lm
colour temperature	2.800K
energy label	

versions



Gradiminisoffitto led retinato chrome
cod 518L



Gradiminisoffitto led retinato satin nickel-plated
cod 520L



Gradiminisoffitto led opalescente chrome
cod 529L



Gradiminisoffitto led opalescente satin nickel-plated
cod 589L



Gradiminisoffitto led tuttopalescente chrome
cod 583L



Gradiminisoffitto led tuttopalescente satin nickel-plated
cod 585L